Revision date: 04.03.2019



SAFETY DATA SHEET

AKPEROX A60

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

ORGANIC PEROXIDES, INITIATORS PAINT DRIERS

Product nameAKPEROX A60Chemical nameMethyl Ethyl Ketone Peroxide1.2. Relevant identified usesthe substance or mixture and uses advised againstIdentified usesIndustrial use.Uses advised againstNo specific uses advised against are identified.1.3. Details of the supplier of the supplier of the substance sheet		
1.2. Relevant identified uses of the substance or mixture and uses advised against Identified usesIndustrial use.Uses advised againstNo specific uses advised against are identified.		
Identified usesIndustrial use.Uses advised againstNo specific uses advised against are identified.		
Uses advised against No specific uses advised against are identified.		
1.3. Details of the supplier of the safety data sheet		
SupplierAKPA KİMYA AMBALAJ SANAYİ VE TİCARET ANONİM ŞİRKETİ Yenibosna Merkez Mah. Ladin Sok. No:36/70 Kat:12 34197 Townofis Bahçelievler, İstanbul, TÜRKİYE Web: www.akpakimya.com TEL: +90 212 580 55 59 FAX: +90 212 580 55 21 E-mail: info@akpakimya.comContact personExport Department - export@akpakimya.com		
1.4. Emergency telephone number		
Emergency telephone AKPA Kimya : +90 212 580 55 59		
SECTION 2: Hazards identification		

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)Physical hazardsOrg. Perox. D - H242Health hazardsAcute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318

Environmental hazards Not Classified

2.2. Label elements

Pictogram

akf





ORGANIC PEROXIDES, INITIATORS PAINT DRIERS



SAFETY DATA SHEET

AKPEROX A60

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Hazard statements	H242 H302 H314	Heating may cause a fire. Harmful if swallowed. Causes severe skin burns and eye damage.
Precautionary statements	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Nosmoking.
	P220	Keep away from amine and cobalt accelerators, acids, alkalis and heavy metalcompounds, combustible materials.
	P234	Keep only in original container
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.	
		Remove contact lenses, if present and easy to do. Continue rinsing.
	P411+P235	Store at temperatures not exceeding (5) – (30)°C. Keep cool.
	P501	Dispose of contents/container in accordance with national regulations.

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Contains

Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients 3.2. Mixtures

Dimethyl Phthalate			%30-60
CAS Number	131-11-3	EC Number	205-011-6
Sınıflandırma T.C. 28848			
Not Classified.			

Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide REACH Reg. No: 01-2119514691-43-0007		%30-60		
CAS Number		1338-23-4	EC Number	700-954-4
Classification				
Org. Perox. D	H242			
Acute Tox. 4	H302			
Acute Tox. 4	H332			
Skin Corr. 1B	H314			
Eye Dam. 1	H318			



ORGANIC PEROXIDES, INITIATORS PAINT DRIERS

SAFETY DATA SHEET

AKPEROX A60

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

201-159-0

SECTION 4: First aid measures

akf

4.1. Description of first aid measures

General information	Effects may be delayed. Keep affected person under observation. Chemical burns must be treated by a physician.		
Inhalation	Remove affected person from source of contamination. Keep affected person warm and at rest. Get medical attention immediately.		
Ingestion	Rinse mouth thoroughly with water. DO NOT induce vomiting. Get medical attention immediately.		
Skin contact	Remove affected person from source of contamination. Immediately remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.		
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately. Continue to rinse.		
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.		
4.2. Most important symptoms and effects, both acute and delayed			
General information	Move out of dangerous ares. Show this Safety data sheet to the doktor in attendance. Do not leave the victim unattended. Symptoms of poisoning may appear several hours later. Call a physician immediately.		
Inhalation	Nausea, vomiting. Dizziness.		
Ingestion	May cause stomach pain or vomiting. Chemical burns.		



SAFETY DATA SHEET

ORGANIC PEROXIDES, INITIATORS PAINT DRIERS

akp

	AKPEROX A60
	COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.
Skin contact	May cause serious chemical burns to the skin.
Eye contact	May cause severe eye irritation.
4.3. Indication of any immedia	ate medical attention and special treatment needed
Notes for the doctor	Treat symptomatically.
SECTION 5: Firefighting meas	ures
5.1. Extinguishing media	
Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing Media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising fro	om the substance or mixture
Specific hazards	Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m ³ . Vapours may form explosive mixtures with air. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous decomposition pro	ducts
	Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.
5.3. Advice for firefighters	
Protective actions during firef	ighting
	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out. Fight fire from safe distance or protected location. Move containers from fire area if it can be done without risk. Do not use water jet as an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.



ORGANIC PEROXIDES, INITIATORS PAINT DRIERS



SAFETY DATA SHEET

AKPEROX A60

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
- Personal precautionsWear protective clothing as described in Section 8 of this safety data sheet. No
smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation
of vapours and contact with skin and eyes. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid or minimise the creation of any environmental contamination.

6.3. Methods and material for containment and cleaning up

Methods for cleaning upKeep combustible materials away from spillage. Eliminate all sources of ignition. No
smoking, sparks, flames or other sources of ignition near spillage. Provide adequate
ventilation. Absorb in vermiculite, dry sand or earth and place into containers.
Wash thoroughly after dealing with a spillage. Do not touch or walk into spilled
material. Wear suitable protective equipment, including gloves, goggles/face
shield, respirator, boots, clothing or apron, as appropriate.

6.4. Reference to other sections

Reference to the other	For personal protection, see Section 8. See Section 11 for additional information on
sections	health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid inhalation of vapours/spray and contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not handle broken packages without protective equipment.

Advice on generalEye wash facilities and emergency shower must be available when handling thisoccupational hygieneproduct. Good personal hygiene procedures should be implemented. Wash hands
and any other contaminated areas of the body with soap and water before leaving
the work site. Good personal hygiene procedures should be implemented.
Mechanical ventilation or local exhaust ventilation may be required. Container
must be kept tightly closed when not in use.

7.2. Conditions for safe storage, including any incompatibilities



ORGANIC PEROXIDES, INITIATORS PAINT DRIERS



SAFETY DATA SHEET

AKPEROX A60

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Storage precautions 7.3. Specific end use(s)	Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents. Store away from the following materials: Acids. Alkalis. Keep away from flammable and combustible materials.
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Dimethyl Phthalate

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³ Short-term exposure limit (15-minute): WEL 10 mg/m³

Methyl ethyl ketone peroxide

Short-term exposure limit (15-minute): WEL 0.2 ppm 1.5 mg/m³

BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m3(Sk)

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment




Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.





ORGANIC PEROXIDES, INITIATORS PAINT DRIERS

ak

SAFETY DATA SHEET

AKPEROX A60

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Hand protection	Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Rubber (natural, latex). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station and safety shower. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Check that the respirator fits tightly and the filter is changed regularly.
Environmental exposure controls	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Colorless.
Odour	Characteristic.
Relative density	1,17±0,005 gr/cm ³ @20°C
Solubility(ies)	Partially soluble in water.
Flammability (solid, gas)	Not applicable
Viscosity	No data avaliable
9.2. Other information	

Active Oxygen Content 9,9 - 10,1%

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity

There are no known reactivity hazards associated with this product.

10.2. Chemical stability



ORGANIC PEROXIDES, INITIATORS Paint driers

akf

SAFETY DATA SHEET

AKPEROX A60

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Stability	Stable at normal ambient temperatures.		
10.3. Possibility of hazardous r	eactions		
Possibility of hazardous reactions	Not available.		
10.4. Conditions to avoid			
Conditions to avoid	Avoid heat, flames and other sources of ignition.		
10.5. Incompatible materials			
Materials to avoid	Strong alkalis. Strong acids. Strong reducing agents. Strong oxidising agents. Some metals.		
10.6. Hazardous decomposition products			
Hazardous decomposition Products	Oxides of carbon. Carbon monoxide (CO). Carbon dioxide (CO2). Hydrocarbons.		
SECTION 11: Toxicological information			
11.1. Information on toxicological effects			
Toxicological information ATE oral (mg/kg)	1,315.0		
Serious eye damage/irritation:	Corrosivity to eyes is assumed.		
Skin corrosion/irritation:	Causes burns.		
Respiratory or skin sensitisatio Respiratory sensitisation	n: Based on available data the classification criteria are not met.		
Germ cell mutagenicity: Genotoxicity - In Vitro - In Vivo	Based on available data the classification criteria are not met.		
Carcinogenicity:	Based on available data the classification criteria are not met.		
Reproductive Toxicity:	Based on available data the classification criteria are not met.		
Reproductive Toxicity – Develo	pment Based on available data the classification criteria are not met.		



ORGANIC PEROXIDES, INITIATORS Paint driers



SAFETY DATA SHEET

AKPEROX A60

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Specific target organ toxicity - single exposure:STOT - Single exposureBased on available data the classification criteria are not met.		
Specific target organ toxicity - repeate STOT - Repeated exposure	ed exposure: Based on available data the classification criteria are not met.	
Aspiration Hazard	Based on available data the classification criteria are not met.	
Inhalation	Harmful by inhalation. May cause damage to mucous membranes in nose, throat, lungs and bronchial system.	
Ingestion	Harmful if swallowed. May cause burns in mucous membranes, throat, oesophagus and stomach.	
Skin contact	Causes burns. Harmful in contact with skin. May cause sensitisation or allergic reactions in sensitive individuals.	
Eye contact	Causes burns.	
Route of entry	Ingestion Inhalation Skin and/or eye contact	
Target organs	Respiratory system, lungs	
Medical considerations	Skin disorders and allergies.	

SECTION 12: Ecological Information

12.1. Toxicity

Ecological information on ingredients	<u>.</u>
	BUTANONE
Acute toxicity - fish	LC₅₀, 96 hours: 3.22 g/l mg/l, Fish
12.2. Persistence and degradability	
Persistence and degradability	The product is readily biodegradable.
12.3. Bio accumulative potential	
Bio accumulative potential	No data available on bioaccumulation.
12.4. Mobility in soil	
Mobility	The product is partly miscible with water and may spread in the aquatic environment.
12.5. Results of PBT and vPvB assessr	nent



ORGANIC PEROXIDES, INITIATORS PAINT DRIERS

ak

SAFETY DATA SHEET

AKPEROX A60

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
12.6. Other adverse effects Other adverse effects	Not available.
SECTION 13: Disposal consider	ations
13.1. Waste treatment method	5
General information	Waste should be treated as controlled waste. Dispose of waste to licensed waste

disposal site in accordance with the requirements of the local Waste Disposal Authority. When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Environmental Manager must be informed of all major spillages.

SECTION 14: Transport in	formation
General information	For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.
14.1. UN number	
UN No. (ADR/RID)	3105
UN No. (IMDG)	3105
UN No. (ICAO)	3105
UN No. (ADN)	3105
14.2. UN proper shipping n	name
Proper Shipping name (ADR/RID)	ORGANIC PEROXIDE TYPE D, LIQUID (Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide)
Proper Shipping name (IMDG)	ORGANIC PEROXIDE TYPE D, LIQUID (Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide)
Proper Shipping name (ICAO)	ORGANIC PEROXIDE TYPE D, LIQUID (Reaction mass of butane-2,2-diyl dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide)



ORGANIC PEROXIDES, INITIATORS PAINT DRIERS



SAFETY DATA SHEET

AKPEROX A60

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Proper Shipping nameORGANICPEROXIDETYPED,LIQUID(Reaction mass of butane-2,2-diyl(ADN)dihydroperoxide and dioxydibutane-2,2-diyl dihydroperoxide)

14.3. Transport hazard class(es)

ADR/RID class	5.2
ADR/RID label	5.2
IMDG class	5.2
ICAO class/division	5.2
ADN class	5.2

Transport labels



14.4. Packing group Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No

14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what todo in the event of an accident or spillage.

EmS	F-J, S-R
ADR transport category	2
Emergency Action Code	2WE
Hazard Identification Number	-
(ADR/RID)	
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk accordingNot Applicable.to Annex II of MARPOL

SECTION 15: Regulatory information



ORGANIC PEROXIDES, INITIATORS Paint driers



SAFETY DATA SHEET

AKPEROX A60

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information	
Key literature references and sources for data	This SDS is prepared based on the information received from the product owner.
Classification procedures according to Regulation (EC) 1272/2008	Skin Corr. 1B - H314; Eye Dam. 1 - H318: Calculation Method. Org. Perox. D - H242: Expert Judgement.
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision comments	Added REACH Number.
Issued By	Gökhan ARDIÇ / CRAD gbf@crad.com.tr +90 216 335 46 00
Issued Date	12.11.2010
Revised By	Simge ARIK lab@akpakimya.com +90 282 361 80 99
Revision date	04.03.2019
Revision	4.0



ORGANIC PEROXIDES, INITIATORS PAINT DRIERS

ak

SAFETY DATA SHEET

AKPEROX A60

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

Hazard statements in full	H225	Highly flammable liquid and vapour.
	H242	Heating may cause a fire.
	H302	Harmful if swallowed.
	H314	Causes severe skin burns and eye damage.
	H318	Causes serious eye damage.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.
	EUH06	6 Repeated exposure may cause skin dryness or cracking.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.